



Party With the King!™

Party King® SWING'N SMOKE™ MVP Grill “Quick Set-Up Guide”

1ST STEPS - Initial Set-up of Prop Legs:

1. Remove safety pin from prop legs hinge.
2. Release the prop legs spring latch by lifting the prop legs slightly, then raising the catch of the spring latch, followed by folding the prop legs downward.
3. With the prop legs in the down/support position, re-insert the safety pin into the hinge to prevent the prop legs from folding back up and losing their support.
4. Adjust height of each prop leg by loosening the L-shaped set screws so that the legs extend downward and come into solid/level contact with the ground.

2ND STEPS - Swinging-Out VERSArm™:

1. Remove security clip from red latch pin (at left side of vehicle's bumper).
2. Lift red pin from latch holes and re-insert safety clip into pin to avoid loss of the clip.
3. **CAUTION:** Do not lay pin on your rear bumper if you have a fold-down tailgate, as it can cause damage to the finish of the tailgate.
4. Grasping grill's side handle, pull the grill out of the latch position, lifting slightly, and slowly swinging-out the VERSArm to the desired grilling position (typically 90° away from the back bumper of your vehicle). Re-adjust heights of prop legs if necessary to level the grill for optimum cooking conditions.

Party With the King!™

www.PartyKingGrills.com
1.877.788.KING (5464)

3RD STEPS - Basic MVP Grill Set-up:

1. Unsnap the grill hood security snaps (one at each end), then raise/open the hood. Remove the 2 side shelves, fuel-tanks holder, and the Double-Barrel Fuel System™ manifold.
2. Install the 2 side shelves by hooking them into the square brackets on each side of the grill. **NOTE:** If you have a ice chest mounted, you will have to remove it to install the left-side shelf. Plastic ice chests should not be left on the VERSArm™ while cooking with the grill!
3. Install the fuel-canister holder by hooking it over the end of the VERSArm™ carrier.
4. Attach two 1.02-lb propane canisters to the Double-Barrel Fuel System™, making sure both manifold valves are in the off/closed position. Do not over-tighten the valves. While applying solid pressure, screw each propane canister into the manifold connectors. Use a little WD-40 lubricant to make the hook-up easier if the tops of the canisters are rusty.

4TH STEPS - Cooking With the MVP Grill:

1. Make certain grill hood is raised/opened and the 3 burner control knobs are in their “off” positions.
2. Open the Double-Barrel Fuel System™ valves to allow propane to flow through the system.
3. Press the black electronic ignition button repeatedly on the left side of the front control panel of the grill.
4. If a clicking noise is heard, then turn-on the middle burner control knob first, while pressing the ignition button. The middle burner should ignite quickly.
5. Once the middle burner has been lighted, turn-on the left and right burner control knobs to ignite the remaining two burners.
6. Once all 3 burners are lit, close the lid and preheat the grill for 10 minutes. Then you're ready to grill!
7. Turn-off all burners and close valves when finished. Reverse instructional steps before traveling. **DO NOT** transport or store propane canisters under the grill hood!